PHOENIX DISPLAY INTERNATIONAL, INC.

# PHOENIX DISPLAY INTERNATIONAL, INC

# SPECIFICATION FOR LCD MODULE

| | |
|---|---|
| **CUSTOMER** | |
| **PART NUMBER** | PDIS080BWX13HP |
| **DESCRIPTION** | 8.0" 800 (RGB) x 1280 Dots |
| **VERSION** | 1.0 |
| **ISSUE DATE** | 02-Apr-19 |

**COMPANY ADDRESS:**
**Phoenix Display International, Inc.**
**6150 W. Gila Springs Place Unit 2**
**Chandler, AZ 85226**
**USA**
**www.phoenixdisplay.com**
**(630) 359-5700 office**
**(630) 359-5701 fax**

## Table of Contents

1. Record of Revision.....3

2. General Specifications.....4

3. Input/OutputTerminals.....5

4. Absolute Maximum Rating.....6

5. Electrical Characteristics.....6

6. Interface Timing.....7

7. Optical Characteristics.....11

8. Environmental / Reliability Tests.....14

9. Mechanical Drawing.....15

10. Packing.....16

11. TFT-LCD Module Inspection Criteria.....17

12. Precautions for Use of LCD modules.....21

## 1. Record of Revision

| Rev | Issued Date | Description | Editor |
|---|---|---|---|
| 1.0 | 2019/4/2 | First Release. | Yigui.Han |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

## 2. General Specifications

| Feature | | Spec |
|---|---|---|
| Characteristics | Size | 8.0 inch |
| | Resolution | 800(horizontal)*1280(Vertical) |
| | Interface | MIPI |
| | Connect type | Connector |
| | Display Colors | 16.7M |
| | Technology type | a-Si |
| | Pixel pitch (mm) | 0.134*0.134 |
| | Pixel Configuration | R.G.B.-Stripe |
| | Display Mode | Normally Black |
| | LCD Driver IC | TBD |
| | Viewing Direction | Full view |
| Mechanical | LCM (W x H x D) (mm) | 114.60*184.10*2.65 |
| | Active Area(mm) | 107.64 x172.22 |
| | Weight (g) | TBD |
| | LED Numbers | 24 LEDs |

Note 1: Requirements on Environmental Protection: RoHs
Note 2: LCM weight tolerance: +/- 5%

# 3. Input/Output Terminals

LCD PIN-MAP

| No. | Symbol | Description |
|---|---|---|
| 1-3 | LED+ | Power for LED backlight(Anode) |
| 4 | NC | No connection |
| 5 | LEDPWM | Backlight on/off control pin |
| 6-8 | LED- | Power for LED backlight(Cathode) |
| 9 | NC | No connection |
| 10 | RESET | Global reset pin |
| 11 | GND | Ground |
| 12 | NC | No connection |
| 13 | D2P | MIPI Data positive signal |
| 14 | GND | Ground |
| 15 | D2N | MIPI Data negative signal |
| 16 | D1P | MIPI Data positive signal |
| 17 | GND | Ground |
| 18 | D1N | MIPI Data negative signal |
| 19 | CLKP | MIPI CLK positive signal |
| 20 | GND | Ground |
| 21 | CLKN | MIPI CLK negative signal |
| 22 | D0P | MIPI Data positive signal |
| 23 | GND | Ground |
| 24 | D0N | MIPI Data negative signal |
| 25 | NC | No connection |
| 26 | GND | Ground |
| 27 | IOVCC | Power supply 1.8V |
| 28 | D3P | MIPI Data positive signal |
| 29 | VCI | Power supply 3.3V |
| 30 | D3N | MIPI Data negative signal |
| 31 | VCI | Power supply 3.3V |
| 32 | GND | Ground |
| 33 | VCI | Power supply 3.3V |
| 34 | NC | No connection |

# 4. Absolute Maximum Rating

| Item | Symbol | MIN | Typ | MAX | Unit | Remark |
|---|---|---|---|---|---|---|
| Supply Voltage | VDD | -0.3 | - | 5 | V | - |
| Operating Temperature | TOPR | 0 | - | 50 | ℃ | - |
| Storage Temperature | TSTG | -10 | - | 60 | ℃ | |

# 5. Electrical Characteristics

## 5.1 Driving TFT LCD Panel

| Item | Symbol | MIN | Typ | MAX | Unit | Remark |
|---|---|---|---|---|---|---|
| **Digital Supply Voltage** | **VDD** | **3.0** | **-** | **3.6** | **V** | |
| **TFT Gate on Voltage** | **VGH** | **7** | **-** | **20** | **V** | |
| **TFT Gate off Voltage** | **VGL** | **-7** | **-** | **-15** | **V** | |
| **Analog power Supply Voltage** | **AVDD** | **4.5** | **-** | **6.3** | **V** | |
| **Gate on-gate off Voltage** | **VGH-VGL** | **14** | **-** | **35** | **V** | |

## 5.2 LED Driving Conditions

| Item | Symbol | MIN | TYP | MAX | Unit | Remark |
|---|---|---|---|---|---|---|
| Forward Current | $I_F$ | - | 160 | - | mA | |
| Forward Voltage | $V_F$ | 16.8 | 18 | 19.2 | V | |
| Backlight Power consumption | $W_{BL}$ | - | 2.88 | - | W | |
| LED Lifetime | | - | 30000 | - | Hrs | |

Note 1: Each LED: IF =20 mA, VF =6+/0.2V.
Note 2: Optical performance should be evaluated at Ta=25℃ only.
Note 3: If LED is driven by high current, high ambient temperature & humidity condition. The life Time of LED will be reduced. Operating life means brightness goes down to 50% initial brightness. Typical operating life time is estimated data.







Figure: LED connection of backlight(Constant Current)

# 6. Interface Timing

## 6.1 DDR clock defintion




## 6.2 Data to timing clock defintion





| Parameter | Description | Min. | Typ. | Max. | Unit | Note |
|---|---|---|---|---|---|---|
| $e_{SPIKE}$ | Input pulse rejection | - | - | 300 | V.ps | 1, 2, 3 |
| $T_{MIN}$ | Minimum pulse width response | 20 | - | - | ns | 4 |
| $V_{INT}$ | Peak-to-peak interference voltage | - | - | 200 | mV | - |
| $f_{INT}$ | Interference frequency | 450 | - | - | MHz | - |


**Note:** (1) Time-voltage integration of a spike above VIL when being in LP-0 state or below VIH when being in LP-1 state
(2) An impulse less than this will not change the receiver state.
(3) In addition to the required glitch rejection, implementers shall ensure rejection of known RF-interferers.
(4) An input pulse greater than this shall toggle the output.

## 6.3 POWER ON/OFF SEQUENCE

BOOSTM[2:1]=01 (Internal DC/DC power mode : PFM, Charge Pump, JD5001)
IOVCC=VCCH=1.65V ~ 3.6V, VCI=VCIP=2.5V ~ 4.8V.
Power on:





Power off:




Fitipower Confidential

## 6.4 Timings for DSI Video mode




| Item | Symbol | Condition | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| Vertical low pulse width | VS | - | 2 | 4 | 200 Note(1) | Line |
| Vertical front porch | VFP | - | 4 | 20 | 200 | Line |
| Vertical back porch | VBP | - | 2 | 10 | 200 Note(1) | Line |
| Vertical blanking period | VBK | VS+VBP+VFP | 8 | 34 | 250 | Line |
| Vertical active area | - | VDISP | - | 1280 | - | Line |
| Vertical Refresh rate | VRR | - | - | 60 | - | Hz |

Confidential

## Horizontal Timings





**Figure 11.10: Horizontal Timing for DSI Video mode I/F**

| Item | Symbol | Condition | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| HS low pulse width | HS | - | 6 | 18 | 78 | DCK |
| Horizontal back porch | HBP | - | 5 | 18 | 78 | DCK |
| Horizontal front porch | HFP | - | 5 | 18 | 78 | DCK |
| Horizontal blanking period | HBLK | HS+HBP+HFP | 16 | 54 (Note1) | 88 | DCK |
| Horizontal active area | HDISP | - | - | 800 | - | DCK |
| Pixel Clock | PCLK | - | 63.06 (Note2) | 67.33 (Note2) | 81.51 (Note2) | MHz |

Note 1: HS+HBP > 0.5us

# 7. Optical Characteristics

| Items | | Symbol | Condition | Min. | Typ. | Max. | Unit | Remark | Note |
|---|---|---|---|---|---|---|---|---|---|
| Response time | | Tr+Tf | - | - | 25 | - | ms | FIG.1 | Note4 |
| Contrast Ratio | | CR | | 600 | 800 | - | - | FIG.2 | Note1 |
| Surface luminance | | LV | θ =0° | 450 | 550 | - | cd/m2 | FIG.2 | Note2 |
| Luminance uniformity | | Yu | θ =0° | - | - | - | % | FIG.2 | Note3 |
| NTSC | | - | θ =0° | - | 55 | - | % | FIG.2 | Note5 |
| Viewing angle | | $\theta_T$ | Center CR≥10 | - | 80 | - | deg | FIG.3 | Note6 |
| | | $\theta_B$ | | - | 80 | - | deg | FIG.3 | |
| | | $\theta_L$ | | - | 80 | - | deg | FIG.3 | |
| | | $\theta_R$ | | - | 80 | - | deg | FIG.3 | |
| Chromaticity | Red | $R_X$ | θ =0° ∅=0° Ta=25° | TBD | TBD | TBD | - | FIG.2 CIE1931 | Note5 |
| | | $R_Y$ | | TBD | TBD | TBD | - | | |
| | Green | $G_X$ | | TBD | TBD | TBD | - | | |
| | | $G_Y$ | | TBD | TBD | TBD | - | | |
| | Blue | $B_X$ | | TBD | TBD | TBD | - | | |
| | | $B_Y$ | | TBD | TBD | TBD | - | | |
| | White | $W_X$ | | TBD | TBD | TBD | - | | |
| | | $W_Y$ | | TBD | TBD | TBD | - | | |

**Note1. Definition of contrast ratio**

Contrast ratio(Cr) is defined mathematically by the following formula. For more information see FIG.2.

$$\text{Contrast ratio} = \frac{\text{Luminance measured when LCD on the “White” state}}{\text{Luminance measured when LCD on the “Black” state}}$$

For contrast ratio, Surface Luminance, Luminance uniformity and CIE,the testing data is base on TOPCON’s BM-5 or BM-7 photo detector or compatible.

**Note2. Definition of surface luminance.**

Surface luminance is the luminance with all pixels displaying white. For more information see FIG.2.

Lv = Average Surface Luminance with all white pixels(P1,P2,P3, ......,Pn)

**Note3. Definition of luminance uniformity**

The luminance uniformity in surface luminance is determined by measuring luminance at each test position 1 through n, and then dividing the maximum luminance of n points luminance by minimum luminance of n points luminance.For more information see FIG.2.

$$YU = \frac{\text{Minimum surface luminance with all white pixels (P1,P2,P3,.....,Pn)}}{\text{Maximum surface luminance with all white pixels (P1,P2,P3,.....,Pn)}}$$

**Note4. Definition of response time**

The response time is defined as the LCD optical switching time interval between “White” state and “Black”state.Rise time (Tr) is the time between photo detector output intensity changed from 90% to 10%. And fall time (Tf) is the time between photo detector output intensity changed from 10% to 90%.

For additional information see FIG1.

**Note5. Definition of color chromaticity (CIE1931)**

CIE (x,y) chromaticity,The x,y value is determined by screen active area center position P5.For more information see FIG.2.

**Note6. Definition of viewing angle**

Viewing angle is the angle at which the contrast ratio is greater than 10. Angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG.3.

For viewing angle and response time testing, the testing data is base on Autronic-Melchers’s ConoScope or DMS series Instruments or compatible.

**FIG.1.The definition of response Time**






**FIG.2. Measuring method for contrast ratio, surface luminance, luminance uniformity, CIE (x,y) chromaticity**

Size : S≤5”(see Figure a) A : 5 mm B : 5 mm
H,V : Active area
Light spot size ∅=5mm(BM-5) or ∅=7.7mm (BM-7)50cm distance or compatible distance from the LCD surface to detector lens.
test spot position : see Figure a.



measurement instrument : TOPCON's luminance meter BM-5 or BM-7 or compatible (see Figure c).

Figure a

Size : 5"＜S≤12.3"(see Figure b) H,V : Active area

Light spot size ∅=5mm(BM-5) or ∅=7.7mm (BM-7)50cm distance or compatible distance from the LCD surface to detector lens.

test spot position : see Figure b.

measurement instrument : TOPCON's luminance meter BM-5 or BM-7 or compatible (see Figure c).





Figure b






Figure c

**FIG.3.The definition of viewing angle**




## 8. Environmental / Reliability Tests

| No | Test Item | Condition | Remarks |
|---|---|---|---|
| 1 | High Temperature Operation | Ts= +50℃, 96hrs | Note 1 IEC60068-2-2, GB2423. 2-89 |
| 2 | Low Temperature Operation | Ta= 0℃, 96hrs | Note 2 IEC60068-2-1 GB2423.1-89 |
| 3 | High Temperature Storage | Ta= +60℃, 96hrs | IEC60068-2-2 GB2423. 2-89 |
| 4 | Low Temperature Storage | Ta= -10℃, 96hrs | IEC60068-2-1 GB/T2423.1-89 |
| 5 | High Temperature & Humidity Storage | Ta= +60℃, 90% RH max,120 hours | IEC60068-2-3 GB/T2423.3-2006 |
| 6 | Thermal Shock (Non-operation) | -10℃ 30 min ~ +60℃ 30 min Change time: 5min, 30 Cycle | Start with cold temperature, end with high temperature IEC60068-2-14, GB2423.22-87 |
| 7 | Electro Static Discharge (Operation) | C=150pF, R=330 Ω, 5 points/panel Air:±8KV, 5 times; Contact: ±4KV, 5 times; (Environment: 15℃ ~ 35℃, 30% ~ 60%, 86Kpa ~ 106Kpa) | IEC61000-4-2 GB/T17626.2-1998 |
| 8 | Vibration (Non-operation) | Frequency range: 10~55Hz, Stroke: 1.mm Sweep: 10Hz~55Hz~10Hz 2 hours for each direction of X .Y. Z. (package condition) | IEC60068-2-6 GB/T2423.5-1995 |
| 9 | Shock (Non-operation) | 60G 6ms, ± X, ±Y , ± Z 3 times for each direction | IEC60068-2-27 GB/T2423.5-1995 |
| 10 | Package Drop Test | Height: 80 cm, 1 corner, 3 edges, 6 surfaces | IEC60068-2-32 GB/T2423.8-1995 |

Note: 1. Ts is the temperature of panel's surface.
2. Ta is the ambient temperature of sample.
3. The size of sample is 5pcs.

# 9. Mechanical Drawing




| PIN | SYMBOL |
|---|---|
| 1 | VLED |
| 2 | VLED |
| 3 | VLED |
| 4 | BC_C |
| 5 | CABC |
| 6 | FB1 |
| 7 | FB2 |
| 8 | FB3 |
| 9 | NC |
| 10 | Reset |
| 11 | GND |
| 12 | NC |
| 13 | D2_P |
| 14 | GND |
| 15 | D2_N |
| 16 | D1_P |
| 17 | GND |
| 18 | D1_N |
| 19 | CLK_P |
| 20 | GND |
| 21 | CLK_N |
| 22 | D0_P |
| 23 | GND |
| 24 | D0_N |
| 25 | NC |
| 26 | GND |
| 27 | LOGIC 1.8V |
| 28 | D3_P |
| 29 | LOGIC 3.3V |
| 30 | D3_N |
| 31 | LOGIC 3.3V |
| 32 | GND |
| 33 | LOGIC 3.3V |
| 34 | NC |

## 10. Packing

**TBD**

# 11. TFT-LCD Module Inspection Criteria

## 11.1 Scope

The incoming inspection standards shall be applied to TFT －LCD Modules (hereinafter Called "Modules") that supplied by CDTech Technology LTD.

## 11.2 Incoming Inspection


The customer shall inspect the modules within twenty calendar days of the delivery date（the “inspection period）at its own cost. The result of the inspection（acceptance or rejection）shall be recorded in writing, and a copy of this writing will be promptly sent to The seller, If the results of the inspecting from buyer does not send to the seller within twenty Calendar days of the delivery date. The modules shall be regards as acceptance. Should the customer fail to notify the seller within the inspection period, the buyers Right to reject the modules shall be lapsed and the modules shall be deemed to have Been accepted by the buyer

## 11.3 Inspection Sampling

3.1. Lot size: Quantity per shipment lot per model
3.2. Sampling type: Normal inspection, Single sampling
3.3. Inspection level: II
3.4. Sampling table: MIL-STD-105E
3.5. Acceptable quality level （AQL ）
Major defect: AQL=0.65 Minor defect: AQL=1.00

## 11.4 Inspection Conditions

4.1 Ambient conditions:
a. Temperature: Room temperature 25±5℃
b. Humidity: (60±10) ％RH
c. Illumination: Single fluorescent lamp non-directive (300 to 700 Lux)
4.2 Viewing distance
The distance between the LCD and the inspector’s eyes shall be at least 35±5 ㎝.
4.3 Viewing Angle
U/D: 45 ° /45°, L/R: 45° /45°





## 11.5 Inspection Criteria



Defects are classified as major defects and minor defects according to the degree of Defectiveness defined herein.

### 11.5.1 Major defect



| Item No | Items to be inspected | Inspection Standard |
|---|---|---|
| 5.1.1 | All functional defects | 1) No display<br>2) Display abnormally<br>3) Short circuit<br>4) line defect |
| `5.1.2 | Missing | Missing function component |
| 5.1.3 | Crack | Glass Crack |


### 11.5.2 Minor defect

| Item No | Items to be inspected | Inspection standard | |
|---|---|---|---|
| 5.2.1 | Spot Defect Including Black spot White spot Pinhole Foreign particle Polarizer dirt | For dark/white spot is defined<br>$\varphi = (x+y) / 2$<br><br> | |
| | | Size φ(mm) | Acceptable Quantity |
| | | φ≤0.2 | Ignore |
| | | 0.2 < Φ≤0.5 | 3 |
| | | 0.3 < Φ | Not allowed |

<table>
<tr><td rowspan="4">5.2.2</td><td rowspan="4">Line Defect<br>Including Black line<br>White line Scratch</td><td colspan="2">Define:<br>
</td></tr>
<tr><td>Width(mm)<br>Length(mm)</td><td>Acceptable Quantity</td></tr>
<tr><td>W≤0.03</td><td>Ignore</td></tr>
<tr><td>0.03 < W≤0.04<br>L≤5.0</td><td>4</td></tr>
<tr><td rowspan="5">5.2.3</td><td rowspan="5">Polarizer<br>Dent/Bubble</td><td>0.04 < W， or L>5.0</td><td>Not allowed</td></tr>
<tr><td>Sizeφ(mm)</td><td>Acceptable Quantity</td></tr>
<tr><td>ϕ ≤0.2</td><td>Ignore</td></tr>
<tr><td>0.2 < ϕ ≤0.3</td><td>3</td></tr>
<tr><td>0.3< ϕ</td><td>Not allowed</td></tr>
<tr><td>Total QTY</td><td>3</td></tr>
<tr><td rowspan="6">5.2.4</td><td rowspan="6">Electrical Dot<br>Defect</td><td colspan="2">Bright and Black dot define:<br>

Two Adjacent Dot</td></tr>
<tr><td colspan="2">Inspection pattern: Full white、Full black、Red、green and blue screens</td></tr>
<tr><td rowspan="2">Item</td><td colspan="3">Acceptable Quantity</td></tr>
<tr><td>I</td><td>O</td><td>Total</td></tr>
<tr><td>Black dot defect</td><td>2</td><td>3</td><td>4</td></tr>
<tr><td>Bright dot defect</td><td>0</td><td>3</td><td>3</td></tr>
<tr><td>Total Dot</td><td>2</td><td>4</td><td>5</td></tr>
</table>

<table>
<tr><td rowspan="5">5.2.5</td><td rowspan="5">Glass defect</td><td colspan="2">1.Corner Fragment:<br>
</td></tr>
<tr><td>Size(mm)</td><td>Acceptable Quantity</td></tr>
<tr><td>X≤3mm<br>Y≤1mm<br>Z≤T</td><td>Ignore<br>T：Glass thickness<br>X: Length<br>Y: Width<br>Z: thickness</td></tr>
<tr><td colspan="2">2. Side Fragment:<br>
</td></tr>
<tr><td>Size(mm)</td><td>Acceptable Quantity</td></tr>
<tr><td>X≤5.0mm<br>Y ≤1mm<br>Z≤T</td><td>T：Glass thickness<br>X: Length<br>Y: Width<br>Z: thickness</td></tr>
</table>



## I area & O area

Note: 1). Dot defect is defined as the defective area of the dot area is larger than 50% of the dot area.

2). The distance between two bright dot defects (red, green, blue, and white) should be larger than 15mm.

3). The distance between black dot defects or black and bright dot defects should be more than 5mm apart.

4). Polarizer bubble is defined as the bubble appears on active display area. The defect of polarizer bubble shall be ignored if the polarizer bubble appears on the outside of active display area.

### 11.6 Mechanics specification

As for the outside dimension, weight of the modules, please refer to product specification For more details

# 12. Precautions for Use of LCD modules

### 12.1 Handling Precautions

12.1.1. The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.

12.1.2. If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.

12.1.3. Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.

12.1.4. The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.

12.1.5. If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:

- Isopropyl alcohol
- Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer. Especially, do not use the following:

- Water
- Ketene
- Aromatic solvents

12.1.6. Do not attempt to disassemble the LCD Module.

12.1.7. If the logic circuit power is off, do not apply the input signals.

12.1.8. To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.

12.1.8.1. Be sure to ground the body when handling the LCD Modules.

12.1.8.2. Tools required for assembly, such as soldering irons, must be properly ground.

12.1.8.3. To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.

12.1.8.4. The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

## 12.2 Storage Precautions

12.2.1. When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

12.2.2. The LCD modules should be stored under the storage temperature range If the LCD modules will be stored for a long time, the recommend condition is:

Temperature : 0℃ ～ 40℃ Relatively humidity: ≤80%

12.2.3. The LCD modules should be stored in the room without acid, alkali and harmful gas.

## 12.3 Transportation Precautions

The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.